SMI CART

PRODUCT BROCHURE

Unit 17 Inospace Tambo Exchange 587 Jones road boksburg

011 397 1176

hello@smicart.co.za

www.smicart.co.za

SMI Z-4 / Z-6

Move smarter, travel further and make every journey more enjoyable with the SMI Cart Z-4. Designed to carry up to four passengers in comfort, this versatile electric cart combines confident performance, rugged styling and effortless mobility—making it an excellent choice for estates, resorts, golf facilities, commercial properties and private leisure use.



SMZ-4 • SMX-4

Model	SMZ-4 / SMX-4
Overall Size	3120 mm × 1330 mm × 2075 mm
Curb Weight (without battery)	≤500 kg
Rated Passenger Capacity	4 passengers
Wheel Distance – Front/Rear	Front: 1020 mm / Rear: 1080 mm
Front and Rear Wheelbase	2115 mm
Minimum Ground Clearance	180 mm
Minimum Turning Radius	≤4.5 m
Maximum Speed	≤25 MPH
Climbing/Holding Ability	20%–45%
Safe Climbing Gradient	20%
Safe Parking Slope Gradient	20%
Range	60–80 miles (normal road conditions)
Braking Distance	≤4 m



SMZ-6 • SMX-6

Model	SMZ-6 / SMX-6
Overall Size	3850 mm × 1360 mm × 2040 mm
Curb Weight (without battery)	≤627 kg
Rated Passenger Capacity	6 passengers
Wheel Distance – Front/Rear	Front: 1020 mm / Rear: 1080 mm
Front and Rear Wheelbase	2880 mm
Minimum Ground Clearance	180 mm
Minimum Turning Radius	≤4.9 m
Maximum Speed	≤25 MPH
Climbing/Holding Ability	20%–45%
Safe Climbing Gradient	20%
Safe Parking Slope Gradient	20%
Range	60–80 miles (normal road conditions)
Braking Distance	≤5 m





Whether you are transporting guests, navigating a large property or simply enjoying the outdoors, the Z-4 is ready to take you there. Contact SMI Cart today to learn more, explore the available options and find the perfect electric cart for your needs.

SMI Z-C2 / Z-C4
Z-L2 Z-L4



SMI CART

SMI2-C2 / SMI2-C4

Discover a versatile range of SMI electric carts designed for smooth, comfortable and dependable transport. With configurations accommodating from two to six passengers, there is a model ready to suit your property, facility or lifestyle.

SM-C2 • SM-C2+2



SMZ-C2

Overall Size	2520 × 1340 × 1895 mm	2950 × 1340 × 1975 mm
Kerb Weight (without battery)	≤365 kg	≤435 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	1662 mm	1662 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.0 m	3.0 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m



SMZ-C2+2

SM-C4 • SM-C4+2



SMZ-C4

Overall Size	3265 × 1340 × 1975 mm	3695 × 1340 × 1975 mm
Kerb Weight (without battery)	≤455 kg	≤530 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	2418 mm	2418 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.3 m	3.3 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMZ-C4+2

SM-L2 • SM-L2+2



SMZ-L2

Overall Size	2520 × 1340 × 2050 mm	2950 × 1340 × 2130 mm
Kerb Weight (without battery)	≤395 kg	≤465 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 1020 mm / Rear: 1085 mm	Front: 1020 mm / Rear: 1085 mm
Wheelbase	1680 mm	1680 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.2 m	3.2 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m



SMZ-L2+2

SM-L4 • SM-L4+2



SMZ-L4

Overall Size	3265 × 1340 × 2130 mm	3695 × 1340 × 2130 mm
Kerb Weight (without battery)	≤485 kg	≤560 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 1020 mm / Rear: 1085 mm	Front: 1020 mm / Rear: 1085 mm
Wheelbase	2436 mm	2436 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.5 m	3.5 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMZ-L4+2

SMI ET-L SERIES



SMI CART

SMIET-L SERIES HUNTING CART

Designed for dependable everyday transport, the SMI Cart ET Series offers a versatile selection of two-, four- and six-passenger models. Choose between standard and elevated configurations to suit estates, resorts, commercial facilities and private properties.

SMET-C2 • SMET-C2+2



SMET-C2

Overall Size	2520 × 1340 × 1895 mm	2950 × 1340 × 1975 mm
Kerb Weight (without battery)	≤380 kg	≤450 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	1662 mm	1662 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.0 m	3.0 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m



SMET-C2+2

SMET-L2 • SMET-L2+2



SMET-L2

Overall Size	2520 × 1340 × 2050 mm	2950 × 1340 × 2130 mm
Kerb Weight (without battery)	≤410 kg	≤480 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 1005 mm / Rear: 1075 mm	Front: 1005 mm / Rear: 1075 mm
Wheelbase	1680 mm	1680 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.2 m	3.2 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m



SMET-L2+2

SMET-C4 • SMET-C4+2



SMET-C4

Overall Size	3265 × 1340 × 1975 mm	3695 × 1340 × 1975 mm
Kerb Weight (without battery)	≤470 kg	≤545 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	2418 mm	2418 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.3 m	3.3 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMET-C4+2

SMET-L4 • SMET-L4+2



SMET-L4

Overall Size	3265 × 1340 × 2130 mm	3695 × 1340 × 2130 mm
Kerb Weight (without battery)	≤500 kg	≤575 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 1005 mm / Rear: 1075 mm	Front: 1005 mm / Rear: 1075 mm
Wheelbase	2436 mm	2436 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.5 m	3.5 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMET-L4+2

SMIET-L SERIES HUNTING CART

SMI UTILITY SERIES



SMI UTILITY SERIES

Built to move more with less effort, the SMI Cart ET Utility Series combines efficient electric performance with practical cargo capacity. Choose from standard or elevated models designed for estates, resorts, maintenance teams, commercial facilities and everyday property operations.



SMET-C300



SMET-C500

SMET-C300 • SMET-C500

Overall Size	2520 × 1340 × 2050 mm	2950 × 1340 × 2130 mm
Kerb Weight (without battery)	≤410 kg	≤480 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 1005 mm / Rear: 1075 mm	Front: 1005 mm / Rear: 1075 mm
Wheelbase	1680 mm	1680 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.2 m	3.2 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m

SMET-L300 • SMET-L500

Overall Size	3265 × 1340 × 1975 mm	3695 × 1340 × 1975 mm
Kerb Weight (without battery)	≤470 kg	≤545 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	2418 mm	2418 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.3 m	3.3 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMET-L300



SMET-L500

SMITS-L HUNTING SERIES CART



SMI CART

SMTS-L HUNTING

Built for the outdoors, the SMI Cart TS Series combines quiet electric operation with rugged capability and dependable performance. Available in two-, four- and six-passenger configurations, these versatile carts are ideal for hunting, game farms, lodges, estates and off-road exploration.

SMTS-C2 • SMTS-C2+2



SMTS-C2

Overall Size	2520 × 1340 × 1895 mm	2950 × 1340 × 1975 mm
Kerb Weight (without battery)	≤365 kg	≤435 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	1662 mm	1662 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.0 m	3.0 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m



SMTS-C2+2

SMTS-C4 • SMTS-C4+2



SMTS-C4

Overall Size	3265 × 1340 × 1975 mm	3695 × 1340 × 1975 mm
Kerb Weight (without battery)	≤455 kg	≤530 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 920 mm / Rear: 1015 mm	Front: 920 mm / Rear: 1015 mm
Wheelbase	2418 mm	2418 mm
Minimum Ground Clearance	100 mm	100 mm
Minimum Turning Radius	3.3 m	3.3 m
Maximum Speed	≤20 MPH	≤20 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMTS-C4+2

SMTS-L2 • SMTS-L2+2



SMTS-L2

Overall Size	2520 × 1340 × 2050 mm	2950 × 1340 × 2130 mm
Kerb Weight (without battery)	≤395 kg	≤465 kg
Passenger Capacity	2 passengers	4 passengers
Wheel Track – Front/Rear	Front: 1020 mm / Rear: 1085 mm	Front: 1020 mm / Rear: 1085 mm
Wheelbase	1680 mm	1680 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.2 m	3.2 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.0 m	<3.0 m



SMTS-L2+2

SMTS-L4 • SMTS-L4+2



SMTS-L4

Overall Size	3265 × 1340 × 2130 mm	3695 × 1340 × 2130 mm
Kerb Weight (without battery)	≤485 kg	≤560 kg
Passenger Capacity	4 passengers	6 passengers
Wheel Track – Front/Rear	Front: 1020 mm / Rear: 1085 mm	Front: 1020 mm / Rear: 1085 mm
Wheelbase	2436 mm	2436 mm
Minimum Ground Clearance	170 mm	170 mm
Minimum Turning Radius	3.5 m	3.5 m
Maximum Speed	≤25 MPH	≤25 MPH
Climbing/Holding Ability	20%–45%	20%–45%
Safe Climbing Gradient	20%	20%
Safe Parking Slope Gradient	20%	20%
Range	60–80 miles (normal road conditions)	60–80 miles (normal road conditions)
Braking Distance	<3.5 m	<3.5 m



SMTS-L4+2



Front seat assembly
(leather can be selected in solid color/contrast color)



2 Seat roof



Folding glass



Steering wheel



Inverted mirror



Ball rack



cooler



Seat armrest



Rear wheel eyebrow



speaker




Dashboard

Side guard plate



Aluminum floor



Front Preposition basket



Four-wheel disc brakes





FEATURES


4/6 Seat roof
Ambient lights
Sound bar
Roof handrail
Sand bottle
Ip66 Waterproof LCD multimedia combination instrument
Rear ball bag rack
Reverse seat assembly
ball washer
Ice bucket
Rear bumper
Rear cover
Double swing arm independent front suspension
High chassis front bumper
Tyre
Rims
(silver, black, gold, red, purple)
Foot pedal

FEATURES

SMI CART



PRODUCT BROCHURE

Unit 17 Inospace Tambo Exchange 587 Jones road boksburg

011 397 1176

hello@smicart.co.za

www.smicart.co.za